




PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A01J 5/04, F16K 11/048 // A01J 7/00, F16K 24/00	A1	(11) International Publication Number: WO 00/56138 (43) International Publication Date: 28 September 2000 (28.09.00)
(21) International Application Number: PCT/SE00/00521 (22) International Filing Date: 17 March 2000 (17.03.00) (30) Priority Data: 9901006-8 19 March 1999 (19.03.99) SE (71) Applicant (for all designated States except US): ALFA LAVAL AGRI AB [SE/SE]; S-147 21 Tumba (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): GUSTAFSSON, Marie-Louise [SE/SE]; Birger Jarlsgatan 104, S-114 20 Stockholm (SE). PETTERSON, Torbjörn [SE/SE]; Rosenhed, S-646 00 Gnesta (SE). (74) Agents: BERGLUND, Stefan et al.; Bjerkéns Patentbyrå KB, Östermalmsgatan 58, S-114 50 Stockholm (SE).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> <i>In English translation (filed in Swedish).</i>
(54) Title: A DEVICE FOR A CONTAINER (57) Abstract <p>The application discloses a device for a container which includes a casing (1) which defines an inner space (2) and an outlet space (3), which extends from the inner space and is connectable to a vacuum source in order to reduce the pressure in the inner space and the outlet space to be lower than the pressure of a surrounding space. The device includes a valve arrangement (8) with a valve seat (9), which forms a first passage (6) between the inner space and the outlet space, a valve element (10), which is abutable against the valve seat for closing the first passage in the first position and is displaceable from the valve seat for opening the passage, and a spindle portion (11) which is connected to the valve element and extends through the valve seat, the outlet space and a second passage (12) through the casing. Means (18, 19) are arranged to form a flow passage, which in the first position of the valve arrangement permits a flow from the surrounding space to the inner space.</p> 		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

5 **A device for a container**

The present invention refers to a device for a container which includes a casing defining an inner space and an outlet space, which extends from the inner space and is
10 arranged to be connected to a vacuum source in such a manner that the pressure in the inner space and the outlet space in a state of use is less than the pressure of a surrounding space outside the casing, wherein the device includes a valve arrangement which includes

- 15 - a first valve seat, which forms a first passage between the inner space and the outlet space,
- a first valve element, which is abutable against the first valve seat for closing the first passage in a first position of the valve arrangement and which is displaceable
20 from the first valve seat to a second position of the valve arrangement for opening the first passage, and
- a spindle portion which is connected to the first valve element and extends through the first valve seat, the outlet space and a second passage through the casing.

25

It is known to use such devices for claws, which includes an outlet pipe connected to a vacuum source and arranged to transport milk from the inner space of the claw to an collecting member of a milking machine. Furthermore, such
30 claws include inlet members, which are arranged to permit the supply of milk from a respective teatcup via a short milk conduit or a teatcup liner. During milking there is a subpressure in the inner space and in the milk conduits. Certain milking machines offer the possibility to detach the
35 teatcups from the teats automatically, wherein the subpressure in the inner space of the claws and the conduits

is removed before the detachment takes place. Since the pressure then will be substantially equal in the inner space of the claw and in the surrounding space, the teatcups will fall off the teats. However, many milking machines do not have any such automatic detachment of the teatcups. The low pressure level in the interior of the claw is thus maintained after the milking is terminated. One such known claw, see for instance WO97/27738, includes a closing valve by which a passage between the inner space of the claw and an outlet space in the outlet pipe may be closed in such a way that no milk flow may flow from the inner space of the claw through the long milk conduit any longer. Furthermore, the low pressure level in the inner space of the claw will increase slowly thanks to an air inlet which permits a certain air inflow from the surrounding space to the inner space of the claw.

However, this air inlet has in the first place another purpose, namely to facilitate the removal of the milk from the inner space of the claw to said collecting member, and therefore has very small dimensions, which means that the pressure between the surrounding space and inner space will be equalised very slowly. Due to this slow pressure equalisation it will take a long time before the teatcups may be detached in an easy manner from the teats.

SUMMARY OF THE INVENTION

The object of the present invention is to remove the problems mentioned above and to provide a device by which the detachment of the teatcups from the teats may be facilitated. In particular, it is aimed at a device by which the pressure between the surrounding space and the inner space of a container, which in a state of use has a very low pressure, may be equalized when the inner space of the container is closed from the pressure reducing source.

This object is obtained by the device initially defined, which is characterized by means which are arranged to form a flow passage which, in the first position of the valve arrangement, permits a flow from the surrounding space to the inner space. By the provision of such a flow passage the pressure in the inner space of the container and the surrounding space will be equalized in a substantially more quick manner than by the technique known up to now. Advantageously, such means are arranged to prevent a flow through the flow passage in the second position of the valve arrangement. In such a way, the flow passage according to the invention will not give rise to any air inflow to the inner space of the container when the valve arrangement is in the open position. For instance, in the case of a claw it is obtained that no air is leaking into the claw during milking. Furthermore, the flow passage is advantageously formed by a channel, which is closed with regard to the outlet space.

According to an embodiment of the invention, the channel extends through the first valve element and the spindle portion. By positioning the channel in this way, the displacement of the valve arrangement between the first position and the second position may be utilized to open and close, respectively the flow passage. Furthermore, such a positioning of the channel requires a small space, which is advantageous with regard to claws.

According to a further embodiment of the invention, the valve arrangement includes a second valve seat, which surrounds the second passage, and a second valve element, which is arranged to abut the second valve seat in said first position for closing the second passage between the outlet space and the surrounding space and which is displaced from the second valve seat in said second

position. By such a second valve element, air is prevented from leaking from the surrounding space into the outlet space when the first valve element is in the closed position. Advantageously, the channel has an orifice in the surrounding space at least when the valve arrangement is in the first position.

According to a further embodiment of the invention, the second valve element extends around the spindle portion. A body of a flexible material may be provided around the spindle portion and form the first valve element and the second valve element. Such a body, for instance of rubber, may in a relatively easy manner be brought to seal against both the first valve seat and the second valve seat. Furthermore, by such a common body for the valve elements the mounting of the valve arrangement is facilitated. Furthermore, the spindle portion may include a groove which extends along the spindle portion and which together with said body forms the channel. Such a groove may be manufactured in a relatively simple manner, wherein the channel is obtained in connection with the mounting of the valve arrangement.

According to a further embodiment of the invention, the spindle portion is connected to a manoeuvre member, which is located in the surrounding space and is arranged to permit manoeuvring of the valve arrangement at least from the first position to the second position. Thereby, the manoeuvring member may be arranged to form a third valve element, which is abutable against a third valve seat which is located on the outer side of the casing and extends around the second passage, wherein the third valve element is arranged to close the second passage when the valve arrangement is in the second position in order to prevent a flow from the surrounding space to the outlet space. The orifice is preferably located on the spindle portion between the third

valve element and the second valve element, i.e. a flow from the surrounding to the inner space is obtained first when the third valve element does not abut the third valve seat.

- 5 The invention is applicable to a container in the form of a claw, which is arranged to be connected to a milking machine via a milk conduit and an outlet space, and to a number of teatcups which are connected to the inner space via the inlet members extending through the casing.

10

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is now to be explained more closely by means of an embodiment, which is described as an example,
15 and with reference to the drawing attached. In the drawing,

Fig 1 discloses schematically a section through a claw having a valve arrangement located in a closed position, and

- 20 Fig 2 a section along the claw in Fig 1 with the valve arrangement in an open position.

DETAILED DESCRIPTION OF AN EMBODIMENT OF THE INVENTION

- 25 The invention is now to be explained by a description of a claw. However, it is to be noted that the invention also is applicable to other types of containers from which for instance a liquid is to be transported by means of a subpressure. For instance, the invention may be applicable
30 to a teatcup which in a container space includes a valve arrangement of the type to be described more closely now.

With reference to Figs 1 and 2, a claw is disclosed, which includes a casing 1, which defines an inner space 2 and an
35 outlet space 3. The part of the casing 1, which defines the outlet space 3, has the shape of an outlet pipe 4 which is

arranged to be connected to a long milk conduit (not disclosed) which in its turn is connected to a vacuum source of a milking machine (not disclosed). Furthermore, the claw includes a number of inlet openings 5, which extend through the casing 1 and only one of which is disclosed in Figs 1 and 2. The inlet openings 5 are arranged to receive a short milk conduit or a teatcup liner (not disclosed) and in such a way connect the inner space 2 of a claw to a respective teatcup (not disclosed). The inner space 2 and the outlet space 3 are connected to each other via a first passage 6, which permits transport of milk from said teatcups through the inlet openings 5 to the inner space 2 and from there to the outlet space 3 and further to a milk collecting member of said milking machine. In order to facilitate transport, which is obtained in a conventional manner by means of said vacuum source, there is an air inlet 7 which extends through the casing 1. The air inlet 7 merely permits a very small air inflow to the inner space 2 and has a cross-sectional diameter which in a typical case is less than 1 mm.

20

In order to stop up the flow from the inner space 2 to the outlet space 3 a valve arrangement 8 is provided. The valve arrangement 8 includes a first valve seat 9, which extends around a first passage 6 between the inner space 2 and the outlet space 3, and a first valve element 10, which is abutable against the first valve seat 9. When the first valve element 10 abuts the first valve seat 9, the valve arrangement 8 is in a first position disclosed in Fig 1. In this first position the flow from the inner space 2 to the outlet space 3 is thus prevented. When the first valve element 10 is displaced from the first valve seat 9, the valve arrangement 8 is in a second position, which is disclosed in Fig 2 and which permits a flow from the inner space 2 to the outlet space 3. The first valve element 10 is provided on a valve spindle 11, which extends through a second passage 12 extending through the casing 1. The valve

spindle 11 is relatively closely held in the second passage 12 so that an annular gap is formed, and is thereby easily displaceable in its longitudinal direction x between the first position and the second position. The displacement of the valve arrangement 8 is obtained partly by means of the pressure relations which arises in different states of operation and partly by means of a manoeuvre member 13, which is provided in a surrounding space outside the casing 1 and which is attached to an outer end of the spindle 11.

10

The valve arrangement 8 also includes a second valve seat 14, which surrounds the second passage 12 and faces the outlet space 3, and a second valve element 15, which is abutable against the second valve seat 14 in order to close the second passage 12 between the outlet space 3 and the surrounding space in such a way that no air can flow in from the surrounding space between the valve spindle 11 and the inner wall of the second passage 14. The first valve element 10 and the second valve element 15 are formed by a common body 16 which is provided on the valve spindle 11. Thereby, the body 16 includes a hole through which the valve spindle 11 extends. The body 16 is manufactured in a flexible material, preferably any rubber-like material. The body 16 is dimensioned in such a way that in the first closed position of the valve arrangement 8 the first valve element 10 will abut sealingly the first valve seat 9 at the same time as the second valve element 15 abuts sealingly the second valve seat 14. As is indicated in the figures, the body 16 is designed in such a way that the part of the body 16 which forms the second valve element 15 extends around the valve spindle 11 at a small distance from the valve spindle 11 in such a way that a thin, annular gap is formed between the valve spindle 11 and the body 16. The gap has a limited extension in the longitudinal direction x of the valve spindle 11. Thanks to this gap the second valve element 15 obtains a certain flexibility in a radial

direction, which facilitates a sealing abutment against the second valve seat 14. As appears from in particular Fig 2, the second valve seat 14 is designed as an annular depression extending around the second passage 12 and being
5 arranged to receive the second, annular valve element 15.

Furthermore, the valve arrangement 8 includes a third valve seat 17, which is located on the outer side of the casing 1 and extends around the second passage 12. Also the manoeuvre
10 member 13 is manufactured by a flexible material, for instance any rubber-like material, and arranged to form a third valve element 18, which is abutable against the third valve seat 17. The third valve element 18 is arranged to abut the third valve seat 17 and thus close the second
15 passage 12 when the valve arrangement 8 is in the second open position. In such a way the third valve element 18 will prevent a flow from the surrounding space to the outlet space 3 and the inner space 2. Air may thus not flow into the claw via the second passage 12 when the valve
20 arrangement 8 is in the open position and consequently, permits transport of milk from the inner space 2 via the outlet space 3 to said milk collecting member.

According to the present invention, the valve arrangement 8
25 includes a flow passage, in the form of a channel 19 which permits a flow from the surrounding space to the inner space 2 when the valve arrangement 8 is in the closed position, which is disclosed in Fig 1. According to the disclosed embodiment, the channel 19 extends through the valve spindle
30 11. More particularly, the channel 19 includes a groove which extends in the valve spindle 11 in its longitudinal direction x. Consequently, the channel 19 is formed by the groove in the valve spindle 11 and the above mentioned hole through the body 16. As appears from the figures, the
35 channel 19 has an orifice which is located in the surrounding space when the valve arrangement 8 is positioned

in this closed position and which is located in the second passage 12 when the valve arrangement 8 is positioned in the open position. The position of the orifice in the open position of the valve arrangement 8 is however not critical
5 since the third valve element 18 abuts sealingly the third valve seat 17 in this open position and in such a way a flow from the surrounding space into the channel 19 is prevented.

The present invention is not limited to the embodiment
10 disclosed but may be varied and modified within the scope of the following claims. It is to be noted, for instance, that the channel 19 may be formed by a hole extending through the valve spindle 11. It is also possible to provide the channel
15 19 in such a way that it extends through the casing 1, wherein it has an orifice towards the surrounding space, which orifice is located in such a way that it may not be reached by a flow from the surrounding space when the third valve element 18 abuts the third valve seat 17.

Claims

1. A device for a container which includes a casing (1) defining an inner space (2) and an outlet space (3), which
5 extends from the inner space and is arranged to be connected to a vacuum source in such a manner that the pressure in the inner space (2) and the outlet space (3) in a state of use is less than the pressure of a surrounding space outside the casing (1), wherein the device includes a valve arrangement
10 (8) which includes
- a first valve seat (9), which forms a first passage (6) between the inner space (2) and the outlet space (3),
- a first valve element (10), which is abutable against the first valve seat (9) for closing the first passage (6)
15 in a first position of the valve arrangement (8) and which is displaceable from the first valve seat (9) to a second position of the valve arrangement (8) for opening the first passage (6), and
- a spindle portion (11) which is connected to the first
20 valve element (10) and extends through the first valve seat (9), the outlet space (3) and a second passage (12) through the casing (1),
characterised by means (18, 19) which are arranged to form a flow passage (19) which, in the first position of the valve
25 arrangement (8), permits a flow from the surrounding space to the inner space (2).

2. A device according to claim 1, characterised in that said means (18, 19) are arranged to prevent a flow through
30 the flow passage (19) in the second position of the valve arrangement (8).

3. A device according to any one of claims 1 and 2, characterised in that the flow passage is formed by a
35 channel (19) which is closed with regard to the outlet space (3).

4. A device according to claim 3, characterised in that the channel (19) extends through the first valve element (10) and the spindle portion (11).

5

5. A device according to any one of the preceding claims, characterised in that the valve arrangement (8) includes a second valve seat (14), which surrounds the second passage (12), and a second valve element (15), which is arranged to
10 abut the second valve seat (14) in said first position in order to close the second passage (12) between the outlet space (3) and the surrounding space and which is displaced from the second valve seat (14) in said second position.

15 6. A device according to claims 4 and 5, characterised in that the channel (19) has an orifice in the surrounding space at least when the valve arrangement (8) is in the first position.

20 7. A device according to any one of claims 5 and 6, characterised in that the second valve element (15) extends around the spindle portion (11).

25 8. A device according to claim (7), characterised by a body (16) of a flexible material, which is provided around the spindle portion (11) and forms the first valve element (10) and the second valve element (15).

30 9. A device according to claims 3 and 8, characterised in that the spindle portion (11) includes a groove, which extends along the spindle portion (11) and which together with said body (16) form the channel (19).

35 10. A device according to any one of the preceding claims, characterised in that the spindle portion (11) is connected to a manoeuvre member (13), which is located in the

surrounding space and arranged to permit manoeuvring of the valve arrangement (8) at least from the first position to the second position.

- 5 11. A device according to claim 10, characterised in that the manoeuvre member (13) is arranged to form a third valve element (18), which is abutable to a third valve seat (17) located on the outer side of the casing (1) and extending around the second passage (12), wherein the third valve
10 element (18) is arranged to close the second passage (12) when the valve arrangement (8) is located in the second position in order to prevent a flow from the surrounding space to the outlet space (3).
- 15 12. A device according to claims 6 and 1, characterised in that the orifice is located on the spindle portion (11), between the third valve element (18) and the second valve element (15).
- 20 13. A valve device according to anyone of the preceding claims, characterised in that the container is a claw.

Fig 1





Fig 2



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/00521

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: A01J 5/04, F16K 11/048 // A01J 7/00, F16K 24/00
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: A01J, F16K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	Derwent's abstract, No 93- 16197/02, week 9302, ABSTRACT OF SU, 1713510 (DNEPR BRANCH UKR CATTLE ARTIF INSEM INST), 23 February 1992 (23.02.92), Figure 1	1-4,6,10,13
Y	Figure 1	11
	--	
Y	SE 212649 C (AB MANUS), 2 May 1967 (02.05.67), figures 1,2	11
	--	
A	US 4023588 A (OLANDER), 17 May 1977 (17.05.77), figures 1,2	1-4,6,10
	--	

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

21 June 2000

Date of mailing of the international search report

18 -07- 2000

Name and mailing address of the ISA/

Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Magnus Thorén/OGU
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/00521

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2564686 A (R.J.GRAY), 21 August 1951 (21.08.51), figure 1 --	1-3,9-11
A	US 4395971 A (HAPPEL ET AL.), 2 August 1983 (02.08.83), column 9, line 36 - line 60, figure 3 --	1-3,9,13
A	WO 9727738 A1 (ALFA LAVAL AGRI AB), 7 August 1997 (07.08.97) -- -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

02/12/99

International application No.

PCT/SE 00/00521

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
SE	212649	C	02/05/67	NONE	
US	4023588	A	17/05/77	CA 1031285 A	16/05/78
				DD 119516 A	05/05/76
				DE 2539404 A	25/03/76
				DK 403575 A	12/03/76
				FR 2284279 A,B	09/04/76
				GB 1519011 A	26/07/78
				NL 7510491 A	15/03/76
				SE 385080 B,C	08/06/76
				SE 7411451 A	12/03/76
US	2564686	A	21/08/51	NONE	
US	4395971	A	02/08/83	DE 2810087 A,C	20/09/79
				FR 2419012 A,B	05/10/79
				DE 2832390 A	14/02/80
WO	9727738	A1	07/08/97	AU 707899 B	22/07/99
				AU 1047597 A	22/08/97
				AU 1681497 A	22/08/97
				AU 5519496 A	18/11/96
				BR 9608230 A	29/12/98
				CA 2245643 A	07/08/97
				EP 0823004 A	11/02/98
				EP 0878995 A	25/11/98
				EP 0957678 A	24/11/99
				NO 983574 A	04/08/98
				SE 511150 C	09/08/99
				SE 9600412 A	06/08/97
				WO 9727736 A	07/08/97